heidolph
research made easy

# Hei-CHILL 350 NR
# **Technical datasheet**

| | |
|---|---|
| **Dimensions (W × H × D)** | 240 x 500 x 400 mm |
| **Weight** | 31 kg |
| **Display** | LED |
| **Working temperature range** | -10°C...40°C |
| **Display resolution** | 0.1°C |
| **Interfaces** | Alarm Output, RS 232 |
| **Resolution** | N/A |
| **Pump flow max.** | 9 L/min |
| **Noise Level** | 57 dB(A) |
| **Pump pressure max.** | 0.4 bar |
| **Power Supply** | 115 V; 60 Hz |
| **Filling Volume (Min)** | 4 L |
| **Filling Volume (Max)** | 7 L |
| **Power Consumption (Max)** | 0.5 kW |
| **Power Plug** | Cold Device Plug (IEC 60320, C14) |
| **Protection Rating** | IP 32 |
| **Temperature Stability** | 0.5 ± K |
| **Refrigerant Stage 1** | R-290 (GWP 3) A3; 0.041 kg; 0.0 t CO2 - eq |
| **In/Outlet** | 8 mm |
| **Safety Fittings** | NFL |

| | |
|---|---|
| **Resolution of Setting** | 0.1°C |
| **Permissible Temperature Range During Storage** | 5°C...40°C |
| **Permissible Temperature Range During Transport** | -20°C...43°C |
| **Protection Class** | 1 |