



Hei-CHILL 3000

Technical datasheet

Dimensions (W × H × D)	550 x 970 x 650
Weight	93 kg
Display	3.5" TFT display (320 x 240 pixels)
Protection class (EN 60529)	IP 32
Acoustic pressure	< 70 (dB(A)) (in accordance with IEC 61010)
Protection class	1
Overvoltage category	II
Operating temperature	-20 to 40 °C
Control accuracy	±0.05 K
Circulation pump	Max. flow rate (L at 1 bar, H ₂ O 20°C): 20 Max. flow pressure (bar, H ₂ O 20°C): 2
Class. acc. DIN 12876	I/NFL
Refrigerant	R-449A
Alarm output connection	max. 30 V DC, 0.2 A
Contamination level	2
Distance to surroundings all around (cm)	50
Cooling	Air-cooled
Refrigerant fill weight max. (kg)	1,1
Thermal fluid fill volume (max./min. (L))	33/20
Standard supply voltage	1 x 230 V (50 Hz) or 1 x 208 - 220 V (60 Hz)

Cooling output (W)	3000
GWP(100a)*	1397
Rated power	230 V 1800 W 208 - 220 V 2300 W
Exhaust air m3/h	1300
CO2 equivalent (t)	1.3
Storage temperature range	-20 to 50 °C