

## Hei-SHAKE Reciprocating Core 2000

### Technical datasheet



<b>Dimensions (W × H × D)</b>	356 x 129 x 403 mm
<b>Weight</b>	approx. 14 kg
<b>Maximum permissible load</b>	15 kg
<b>Drive</b>	EC Motor
<b>Speed range</b>	1 - 300 rpm
<b>Acoustic pressure</b>	< 85 dB (A), in accordance with IEC 61010
<b>Rated voltage</b>	1/N/PE 100-240 V, AC 50/60 Hz
<b>Overvoltage category</b>	N/A
<b>Degree of pollution</b>	N/A
<b>Power input</b>	90 W
<b>Operating temperature</b>	5 °C – 31 °C at up to 80 % rel. humidity
<b>Installation altitude</b>	up to 2,000 m asl
<b>Overheat protection</b>	N/A
<b>Speed control</b>	N/A
<b>Usable area</b>	(W x D) 390 × 340 mm
<b>Movement</b>	reciprocating (horizontal shaking motion)
<b>Orbit</b>	N/A
<b>Fuse</b>	N/A
<b>Permissible mains voltage fluctuations</b>	N/A
<b>Bottle dimensions</b>	N/A
<b>Interfaces</b>	N/A

**Protection Class**

IP32 (acc. to EN 60529)