Hei-SHAKE Reciprocating Core

# Technical datasheet



| | |
|---|---|
| **Dimensions (W × H × D)** | 356 x 129 x 403 mm |
| **Weight** | approx. 14 kg |
| **Maximum permissible load** | 15 kg |
| **Drive** | EC Motor |
| **Speed range** | 1 - 300 rpm |
| **Acoustic pressure** | < 85 dB (A), in accordance with IEC 61010 |
| **Rated voltage** | 1/N/PE 100-240 V, AC 50/60 Hz |
| **Overvoltage category** | N/A |
| **Degree of pollution** | N/A |
| **Power input** | 90 W |
| **Operating temperature** | 5 °C – 31 °C at up to 80 % rel. humidity |
| **Installation altitude** | up to 2,000 m asl |
| **Overheat protection** | N/A |
| **Speed control** | N/A |
| **Usable area** | (W x D) 294 × 263 mm |
| **Movement** | reciprocating (horizontal shaking motion) |
| **Orbit** | N/A |
| **Fuse** | N/A |
| **Permissible mains voltage fluctuations** | N/A |
| **Bottle dimensions** | N/A |
| **Interfaces** | N/A |

| | |
|---|---|
| **Protection Class** | IP32 (acc. to EN 60529) |