

Reax 20 - for 4 bottles (1-16 rpm)

Technical datasheet



| | |
|------------------------------------|--|
| Dimensions (W × H × D) | 490 × 520 × 465 |
| Weight | 23 kg |
| Maximum permissible load | 30 kg |
| Drive | Asynchronous motor |
| Speed range | 1 – 16 rpm; Speed display: scale |
| Protection class (EN 60529) | IP21 |
| Acoustic pressure | < 45 dB (A), in accordance with IEC 61010 |
| Rated voltage | 230 V, 50/60 Hz 115 V, 60 Hz |
| Protection class | I |
| Overvoltage category | n.a. |
| Degree of pollution | n.a. |
| Power input | 280 W |
| Operating temperature | 5 °C – 31 °C at up to 80 % rel. humidity 32 °C – 40 °C at up to 50 % rel. humidity (decreasing linearly) |
| Installation altitude | up to 2,000 m asl |
| Overheat protection | self-resetting |
| Speed control | electronic |
| Usable area | n.a. |
| Movement | vertically rotating |
| Orbit | n.a. |

Fuse

T3, 15 A (230 V) | T6, 25 A (115 V)

**Permissible mains voltage
fluctuations**

n.a.

Bottle dimensions

Maximum bottle diameter: 136 mm | Maximum bottle
height: 270 mm