

## Reax top

### Technical datasheet



<b>Dimensions (W × H × D)</b>	134 x 105 x 172 mm
<b>Weight</b>	2.8 kg
<b>Maximum permissible load</b>	n.a.
<b>Drive</b>	shaded pole motor
<b>Speed range</b>	100 – 2,500 rpm; 200 – 3,200 rpm
<b>Protection class (EN 60529)</b>	IP 22
<b>Acoustic pressure</b>	< 50 up to 2,500 rpm; < 58 up to 3,200 rpm
<b>Rated voltage</b>	230 V 50 Hz; 230 V 60 Hz; 115 V 60 Hz
<b>Protection class</b>	1
<b>Overvoltage category</b>	n.a.
<b>Degree of pollution</b>	n.a.
<b>Power input</b>	51 W
<b>Operating temperature</b>	n.a.
<b>Installation altitude</b>	n.a.
<b>Overheat protection</b>	self-resetting
<b>Speed control</b>	scale with reference points
<b>Usable area</b>	n.a.
<b>Movement</b>	circular vibrating
<b>Orbit</b>	5 mm
<b>Fuse</b>	n.a.
<b>Permissible mains voltage fluctuations</b>	n.a.

**Bottle dimensions**

n.a.

**Interfaces**