heidolph
research made easy

# Multi Reax
# **Technical datasheet**



| | |
|---|---|
| **Dimensions (W × H × D)** | 270 × 172 × 410 mm |
| **Weight** | approx. 10 kg |
| **Maximum permissible load** | 1.5 kg |
| **Drive** | Asynchronous motor |
| **Speed range** | 150 – 2,000 rpm; Indicator: digital |
| **Acoustic Pressure** | < 45 dB (A), in accordance with IEC 61010 |
| **Rated Voltage** | 230 V / 50 Hz, 110 V / 60 Hz |
| **Overvoltage Category** | n.a. |
| **Degree of Pollution** | n.a. |
| **Power input** | 50 W |
| **Operating temperature** | 5 °C – 31 °C at up to 80 % rel. humidity \| 32 °C – 40 °C at up to 50 % rel. humidity (decreasing linearly) |
| **Installation Altitude** | up to 2,000 m asl |
| **Overheat protection** | self-resetting |
| **Speed control** | n.a. |
| **Usable area** | n.a. |
| **Movement** | circular vibrating |
| **Orbit** | 3 mm |
| **Fuse** | n.a. |
| **Permissible Mains Voltage fluctuations** | n.a. |

| | |
|---|---|
| **Bottle dimensions** | n.a. |
| **Interfaces** | |
| **Protection Class** | |