

Hei-CHILL 5000

Technical datasheet



| | |
|--|---|
| Dimensions (W × H × D) | 550 x 970 x 650 |
| Weight | 98 kg |
| Display | 3.5" TFT display (320 x 240 pixels) |
| Protection class (EN 60529) | IP 32 |
| Acoustic pressure | < 70 (dB(A)) (in accordance with IEC 61010) |
| Protection class | 1 |
| Overvoltage category | II |
| Operating temperature | -20 to 40 °C |
| Control accuracy | ±0.05 K |
| Circulation pump | Max. flow rate (L at 1 bar, H ₂ O 20°C): 20 Max. flow pressure (bar, H ₂ O 20°C): 2 |
| Class. acc. DIN 12876 | I/NFL |
| Refrigerant | R-449A |
| Alarm output connection | max. 30 V DC, 0.2 A |
| Contamination level | 2 |
| Distance to surroundings all around (cm) | 50 |
| Cooling | Air-cooled |
| Refrigerant fill weight max. (kg) | 1,1 |
| Thermal fluid fill volume (max./min. (L)) | 33/20 |
| Standard supply voltage | |

1 x 400 V 3/N/PE (50 Hz) or 1 x 208 - 220 V 3/PE (60 Hz)

Cooling output (W) 5000

GWP(100a)* 1397

Rated power 400 V 3300 W | 208 - 220 V 3600 W

Exhaust air m3/h 2500

CO2 equivalent (t) 1.5

Storage temperature range -20 to 50 °C