

## Reax 20 - for 8 bottles (1-16 rpm)

### Technical datasheet



<b>Dimensions (W × H × D)</b>	770 × 520 × 465
<b>Weight</b>	28 kg
<b>Maximum permissible load</b>	30 kg
<b>Drive</b>	Asynchronous motor
<b>Speed range</b>	1 – 16 rpm; Speed display: scale
<b>Protection class (EN 60529)</b>	IP21
<b>Acoustic pressure</b>	< 45 dB (A), in accordance with IEC 61010
<b>Rated voltage</b>	230 V, 50/60 Hz   115 V, 60 Hz
<b>Protection class</b>	I
<b>Overvoltage category</b>	n.a.
<b>Degree of pollution</b>	n.a.
<b>Power input</b>	280 W
<b>Operating temperature</b>	5 °C – 31 °C at up to 80 % rel. humidity   32 °C – 40 °C at up to 50 % rel. humidity (decreasing linearly)
<b>Installation altitude</b>	up to 2,000 m asl
<b>Overheat protection</b>	self-resetting
<b>Speed control</b>	electronic
<b>Usable area</b>	n.a.
<b>Movement</b>	vertically rotating
<b>Orbit</b>	n.a.

**Fuse**

T3, 15 A (230 V) | T6, 25 A (115 V)

**Permissible mains voltage  
fluctuations**

n.a.

**Bottle dimensions**

Maximum bottle diameter: 136 mm | Maximum bottle  
height: 270 mm