

# Hei-Mix S

## Technical datasheet



|   |   |
|---|---|
| <b>Dimensions (W × H × D)</b>             | 126 × 80 × 140 mm                         |
| <b>Usable surface heating plate</b>       | 104 mm stirrer plate                      |
| <b>Weight</b>                             | 1.1 kg                                    |
| <b>Maximum permissible load</b>           | 6 kg                                      |
| <b>Drive</b>                              | shaded pole motor                         |
| <b>Speed range</b>                        | 0 – 2.200 rpm                             |
| <b>Heating power</b>                      | n.a.                                      |
| <b>Heating temperature range</b>          | n.a.                                      |
| <b>Heating control</b>                    | n.a.                                      |
| <b>Temperature measurement accuracy</b>   | n.a.                                      |
| <b>Temperature measurement resolution</b> | n.a.                                      |
| <b>Display</b>                            | n.a.                                      |
| <b>Protection class (EN 60529)</b>        | IP 21                                     |
| <b>Acoustic pressure</b>                  | < 70 db(A) (in accordance with IEC 61010) |
| <b>Rated voltage</b>                      | n.a.                                      |
| <b>Connection</b>                         | n.a.                                      |
| <b>Protection class</b>                   | 2   |
| <b>Overvoltage category</b>               | n.a.                                      |
| <b>Degree of pollution</b>                | n.a.                                      |
| <b>Power input</b>                        | n.a.                                      |
| <b>EMC class</b>                          | n.a.                                      |

**Operating temperature**

n.a.

**Installation altitude**

n.a.