heidolph
research made easy

# Hei-SHAKE Orbital Core
# **Technical datasheet**



| | |
|---|---|
| **Dimensions (W × H × D)** | 356 × 129 × 403 mm |
| **Weight** | approx. 14 kg |
| **Maximum permissible load** | max. 15 kg |
| **Drive** | EC motor |
| **Speed range** | 1 – 530 rpm |
| **Acoustic pressure** | < 85 dB (A), in accordance with IEC 61010 |
| **Rated voltage** | 100 – 240 V, 50/60 Hz |
| **Overvoltage category** | n.a. |
| **Degree of pollution** | n.a. |
| **Power input** | 90 W |
| **Operating temperature** | 5 °C – 31 °C up to 80 % rel. humidity \| 32 °C – 40 °C up to 50 % rel. humidity (decreasing linearly) |
| **Installation altitude** | up to 2,000 m asl |
| **Overheat protection** | n.a. |
| **Speed control** | n.a. |
| **Usable area** | 294 × 263 mm |
| **Movement** | orbital |
| **Orbit** | 20 mm |
| **Fuse** | n.a. |
| **Permissible mains voltage fluctuations** | n.a. |
| **Bottle dimensions** | n.a. |

| | |
|---|---|
| **Interfaces** | 1 × RS232 (Sub-D, 9 pole) |
| **Protection Class** | |