

## Reax 20 - for 8 bottles (2-32 rpm)

### Technical datasheet



|                                    |  |
|------------------------------------|--|
| <b>Dimensions (W × H × D)</b>      | 770 × 520 × 465  |
| <b>Weight</b>                      | 28 kg  |
| <b>Maximum permissible load</b>    | 30 kg  |
| <b>Drive</b>                       | Asynchronous motor   |
| <b>Speed range</b>                 | 2 – 32 rpm; Speed display: scale   |
| <b>Protection class (EN 60529)</b> | IP21   |
| <b>Acoustic pressure</b>           | < 45 dB (A), in accordance with IEC 61010  |
| <b>Rated voltage</b>               | 230 V, 50/60 Hz   115 V, 60 Hz   |
| <b>Protection class</b>            | I  |
| <b>Overvoltage category</b>        | n.a.   |
| <b>Degree of pollution</b>         | n.a.   |
| <b>Power input</b>                 | 280 W  |
| <b>Operating temperature</b>       | 5 °C – 31 °C at up to 80 % rel. humidity   32 °C – 40 °C at up to 50 % rel. humidity (decreasing linearly) |
| <b>Installation altitude</b>       | up to 2,000 m asl  |
| <b>Overheat protection</b>         | self-resetting   |
| <b>Speed control</b>               | electronic   |
| <b>Usable area</b>                 | n.a.   |
| <b>Movement</b>                    | vertically rotating  |
| <b>Orbit</b>                       | n.a.   |

**Fuse**

T3, 15 A (230 V) | T6, 25 A (115 V)

**Permissible mains voltage  
fluctuations**

n.a.

**Bottle dimensions**

Maximum bottle diameter: 136 mm | Maximum bottle  
height: 270 mm