heidolph
research made easy

# Vibramax 100
# **Technical datasheet**



| | |
|---|---|
| **Dimensions (W × H × D)** | 245 × 125 × 310 mm |
| **Weight** | 5.5 kg |
| **Maximum permissible load** | 2 kg |
| **Drive** | Shaded pole motor |
| **Speed range** | 150 – 2,500 rpm |
| **Acoustic Pressure** | < 50 dB (A) |
| **Rated Voltage** | |
| **Overvoltage Category** | II |
| **Degree of Pollution** | 2 |
| **Power input** | 31 W |
| **Operating temperature** | 5 °C – 31 °C up to 80 % rel. humidity \| 32 °C – 40 °C up to 50 % rel. humidity (decreasing linearly) |
| **Installation Altitude** | up to 2,000 m asl |
| **Overheat protection** | self-resetting |
| **Speed control** | analogue |
| **Usable area** | 220 × 220 mm |
| **Movement** | circular vibrating |
| **Orbit** | 3 mm |
| **Fuse** | M 1,25 A (230 V) or T 2,0 A (115 V) |
| **Permissible Mains Voltage fluctuations** | ±10 % |
| **Bottle dimensions** | n.a. |

| | |
|---|---|
| **Interfaces** | n.a. |
| **Protection Class** | |