Polymax 1040 (ángulo de inclinación de 5°)
# Technical datasheet



| | |
|---|---|
| **Dimensions (W × H × D)** | 320 × 195 × 375 mm |
| **Weight** | approx. 8 kg |
| **Maximum permissible load** | 5 kg |
| **Drive** | Asynchronous motor |
| **Speed range** | 2 – 50 rpm |
| **Acoustic Pressure** | < 50 dB (A), in accordance with IEC 61010 |
| **Rated Voltage** | 230 V, 50 Hz or 115 V, 60 Hz |
| **Overvoltage Category** | n.a. |
| **Degree of Pollution** | n.a. |
| **Power input** | 115 W |
| **Operating temperature** | 5 °C – 31 °C up to 80 % rel. humidity \| 32 °C – 40 °C up to 50 % rel. humidity (decreasing linearly) |
| **Installation Altitude** | up to 2,000 m asl |
| **Overheat protection** | self-resetting |
| **Speed control** | n.a. |
| **Usable area** | 290 × 258 mm |
| **Movement** | waving, 5° |
| **Orbit** | n.a. |
| **Fuse** | M 1,25 A (230 V) or T 2,0 A (115 V) |
| **Permissible Mains Voltage fluctuations** | n.a. |
| **Bottle dimensions** | n.a. |

| | |
|---|---|
| **Interfaces** | n.a. |
| **Protection Class** | |