

## Reax 2 con adaptador universal

### Technical datasheet



<b>Dimensions (W × H × D)</b>	501 × 235 × 180 mm
<b>Weight</b>	approx. 5 kg
<b>Maximum permissible load</b>	1 kg
<b>Drive</b>	Shaded pole motor
<b>Speed range</b>	20 – 200 rpm; Indicator: analogue
<b>Protection class (EN 60529)</b>	IP21
<b>Acoustic pressure</b>	< 45 (dB(A)) (in accordance with IEC 61010)
<b>Rated voltage</b>	230-240 V (50 Hz) or 115 V (60 Hz)
<b>Protection Class</b>	I
<b>Overvoltage category</b>	n.a.
<b>Degree of pollution</b>	n.a.
<b>Power input</b>	33 W max.
<b>Operating temperature</b>	n.a.
<b>Installation altitude</b>	n.a.
<b>Overheat protection</b>	self reset function
<b>Speed control</b>	electronic
<b>Usable area</b>	230 × 160 mm
<b>Movement</b>	Overhead rotation
<b>Orbit</b>	n.a.
<b>Fuse</b>	n.a.
<b>Permissible mains voltage fluctuations</b>	n.a.

**Bottle dimensions**

n.a.

**Interfaces**

n.a.