

## Hei-VAC Valve Industrial

### Technical datasheet



<b>Dimensions (l × h × p)</b>	326 x 243 x 402 mm
<b>Poids</b>	17.3 kg
<b>Classe de protection (EN 60529)</b>	IP 40
<b>Type de raccordement</b>	Coolant: hose nozzle DN 6-8 mm
<b>Température de service</b>	+10 - +40°C
<b>Protection du moteur</b>	thermal cutout, manual reset
<b>Storage temperature range</b>	-10 - +60°C
<b>Puissance</b>	Electrical: 0.25 kW
<b>Maximum pumping speed</b>	3.4 / 3.8 m <sup>3</sup> /h
<b>Ultimate vacuum (absolute)</b>	without gas ballast: 1.5 mbar   with gas ballast: 3 mbar
<b>Maximum permissible pressure</b>	1.1 bar
<b>Permissible relative atmospheric moisture during operation (no condensation)</b>	30% - 85%
<b>Maximum no-load speed</b>	1500 / 1800 min <sup>-1</sup>
<b>Inlet</b>	hose nozzle DN 8 mm
<b>Outlet</b>	hose nozzle DN 8-10 mm
<b>Maximum permissible range of supply voltage (±10%)</b>	100-115 V~ 50/60 Hz, 120 V~ 60 Hz / 200-230 V~ 50/60 Hz