

## Hei-Vac Valve Industrial

### Technical datasheet



|   |   |
|---|---|
| <b>Dimensions (l × h × p)</b>   | 326 x 243 x 402 mm  |
| <b>Poids</b>  | 17.3 kg   |
| <b>Classe de protection (EN 60529)</b>  | IP 40   |
| <b>Type de raccordement</b>   | Coolant: hose nozzle DN 6-8 mm                              |
| <b>Température de service</b>   | +10 - +40°C   |
| <b>Protection du moteur</b>   | thermal cutout, manual reset                                |
| <b>Storage temperature range</b>  | -10 - +60°C   |
| <b>Puissance</b>  | Electrical: 0.25 kW   |
| <b>Maximum pumping speed</b>  | 3.4 / 3.8 m <sup>3</sup> /h                                 |
| <b>Ultimate vacuum (absolute)</b>   | without gas ballast: 1.5 mbar   with<br>gas ballast: 3 mbar |
| <b>Maximum permissible pressure</b>   | 1.1 bar   |
| <b>Permissible relative atmospheric moisture during operation (no condensation)</b> | 30% - 85%   |
| <b>Maximum no-load speed</b>  | 1500 / 1800 min <sup>-1</sup>                               |
| <b>Inlet</b>  | hose nozzle DN 8 mm   |
| <b>Outlet</b>   | hose nozzle DN 8-10 mm                                      |
| <b>Maximum permissible range of supply voltage (±10%)</b>                           | 100-115 V~ 50/60 Hz, 120 V~ 60 Hz<br>/ 200-230 V~ 50/60 Hz  |